



DATA DISPLAY GROUP

DATASHEET

106.7 cm (42") POS-LINE MONITOR

www.datadisplay-group.com

Displays in the POS-Line large series are available in screen diagonal sizes 31.5", 42", 46", 54.6" and 64.5". These models are extensively configurable, and there is a variety of controller types to choose from. The version supplied with an integrated Core-iPC has a removable PC-Box. If needed, for example for servicing purposes, the complete PC can be exchanged without having to take the monitor down from the wall.

- Display for build-in, wall and ceiling
- Various bezels and designs
- High quality LCD panels with LED backlight
- Optional with safety glass or touch
- Video-Controller or integrated PCs
- Removable PC Box for Core-i CPUs
- Portrait or landscape
- VESA
- Robust metal chassis



Panel and housing

| | | |
|-------------------------|----------------------|---|
| Panel Diagonal | [mm] / [Inch] | 1066.8/ 42.0" |
| Type | | Open -frame monitor (various bezels, true-flat glass and touch solutions are available under options) |
| Resolution | [Pixel] | 1920 x 1080 FHD |
| Luminance (center) | [cd/m ²] | 700 |
| Viewing angle | [°] | 178 h / 178 v |
| Backlight | | LED |
| Active area (H/V) | [mm] | 930.24 x 523.26 |
| Number of colors | [M] | 1073.7 (PME, PIII, VP) 16.7 (IQ Ontario, IQ Core-i) |
| Contrast ratio | | 4000:1 |
| Response time (on/off) | [ms] | 8 |
| Pixel class | | ISO 9241-307 (pixel error class II) |
| Life time back light | [h] | 50.000 |
| Mounting | [mm] | VESA MIS-F 400 x 400 (M6) |
| Storage temperature | [°C] / [°F] | -20 ~ 60 / -4 ~ 140 |
| Operating temperature | [°C] / [°F] | 0 ~ 40/ 32 ~ 104 |
| Operating humidity | [%] | 10 ~ 90 (non condensing) |
| Panel orientation | | Landscape and Portrait |
| Location of connectors | | Landscape: bottom Portrait: left (front view) |
| Location of OSD buttons | | Landscape: bottom Portrait: left (front view) |
| Housing | | Coated sheet steel, black RAL 9005 |
| Power supply | [V] | AC 100 - 240/ 50-60 Hz |
| Conformity | | CE, FCC Class A, EU-RoHS |

POS-Line 42.0"




Open frame monitor

VGA, HDMI, DisplayPort

POS-Line 42.0" Video PME


| | | |
|--------------------------|------------|--|
| Order number | | DS-91-478 |
| Interfaces | | 1 x VGA, 1 x HDMI, 1 x DisplayPort, 1 x Audio Line-Out, 1 x USB-Remote |
| Power consumption (typ.) | [Watt] | 100 |
| Weight | [kg/ lb] | 20.0/ 44.09 |
| Dimensions (W x H x D) | [mm/ inch] | 991 x 583 x 109 39.01 x 22.95 x 4.29 |



VGA, DVI, S-Video, CVBS

POS-Line 42.0" Video PIII A


| | | |
|--------------------------|------------|--|
| Order number | | DS-91-479 |
| Interfaces | | 1 x VGA, 1 x DVI (HDMI via DVI), 1 x S-Video; 1 x Composite Video; 1 x RS232; 1 x OSD 4 button |
| Power consumption (typ.) | [Watt] | 100 |
| Weight | [kg/ lb] | 20.0/ 44.09 |
| Dimensions (W x H x D) | [mm/ inch] | 991 x 583 x 109 39.01 x 22.95 x 4.29 |



Network Mediaplayer

POS-Line 42.0" VideoPoster


| | | |
|--------------------------|------------|---|
| Order number | | DS-91-481 |
| Interfaces | | 1 x LAN, 1 x USB, 1 x HDMI, 1 x Line out, 1 x Line in, 1 x SD card slot |
| Power consumption (typ.) | [Watt] | 100 |
| Weight | [kg/ lb] | 20.0/ 44.09 |
| Dimensions (W x H x D) | [mm/ inch] | 991 x 583 x 109 39.01 x 22.95 x 4.29 |




PC AMD Ontario

POS-Line 42.0" IQ Ontario

| | | |
|------------------------|------------|--|
| Order number | | DS-91-480 |
| Interfaces | | 1 x LAN, 4 x USB 2.0, 1 x HDMI, 1 x Audio |
| PC | | CPU: AMD Ontario G-series, T56N, passive cooling Graphics: AMD Radeon HD 6320 RAM: 4GB PC3-8500 (DDR3) ; HD: SSD SATA 120 GB |
| Fan | | No |
| Power consumption | [Watt] | 105 |
| Weight | [kg/ lb] | 20.3/ 44.75 |
| Dimensions (W x H x D) | [mm/ inch] | 991 x 583 x 109 39.01 x 22.95 x 4.29 |




PC Intel Core-i



POS-Line 42.0" IQ Core-i

| | | | |
|------------------------|------------|--|---|
| Order number | | DS-91-523 | DS-91-527 |
| Core-i | | i3 | i5 |
| Interfaces | | VGA, DVI, 2x RS232, 2x Ethernet RJ45, 4x USB 2.0, 4x USB 3.0, 3x Audio Jack 3,5mm, 2x PS2 for Mouse and Keyboard | |
| PC | | CPU: Intel® Core-i3-(4 x 2.4 GHz), Grafik Intel HD 4000, RAM: 4GB DDR 3 Storage: 120 GB SSD | CPU: Intel® Core-i5 (4 x 3.2 GHz), Grafik Intel HD 4000, RAM: 4GB DDR 3 Storage: 120 GB SSD |
| Fan | | Fanless operation | |
| Power consumption | [Watt] | 125 | |
| Weight | [kg/ lb] | 23.5/ 51.81 | |
| Dimensions (W x H x D) | [mm/ inch] | 991 x 583 x 109 39.01 x 22.95 x 4.29 | |



Bezels

| | | | |
|---|------------|---|--|
| Order number | | DS-91-494 | DS-91-613 |
| Name | | Front bezel | Aluminium bezel |
| Finish | | Steel, powdered, black RAL 9005 | Aluminum, brushed, silver RAL 9006 |
| Can be combined with | | Touch, safety glass | |
| Weight | [kg/ lb] | 1.50/ 3.30 | 4.10/ 9.04 |
| Dimensions of monitor with option (W x H x D) | [mm/ inch] | 994 x 587 x 111 39.13 x 23.11 x 4.37 | 1019 x 612 x 122 40.12 x 24.09 x 4.80 |


| | | | |
|---|------------|---|--|
| Order number | | DS-91-561 | DS-91-917 |
| Name | | TrueFlat bezel with glass | TrueFlat bezel with touch |
| Finish | | Sheet steel, RAL 9006 glare (aluminium white), safety glass TSG 4 mm, anti-glare, printed black passepartout (RAL 9005) | Sheet steel, RAL 9006 glare (aluminium white), safety glass TSG 4 mm, anti-glare, printed black passepartout (RAL 9005) with PCAP touch, 10 touch points (next page) |
| Can be combined with | | — | |
| Weight | [kg/ lb] | 12.0/ 26.45 | |
| Dimensions of monitor with option (W x H x D) | [mm/ inch] | 1021 x 614 x 116 40.20 x 24.17 x 4.57 | |

Glass*

| | | | |
|---|------------|---|--|
| Order number | | DS-91-502 | DS-91-499 |
| Name | | Safety glass | TrueFlat glass |
| Glass | | Safety glass TSG, 4 mm anti glare | Safety glass TSG, 4 mm anti glare, printed black passepartout (RAL 9005) |
| Can be combined with | | Front bezel, Aluminium bezel | — |
| Weight | [kg/ lb] | 5.3/ 11.68 | 7.5/ 16.53 |
| Dimensions of monitor with option (W x H x D) | [mm/ inch] | 991 x 583 x 114 39.01 x 22.95 x 4.49 | 1013 x 606 x 115 39.88 x 23.86 x 4.53 |

*Cover glass and touches will reduce monitor brightness.

Options



Front bezel is a metal bezel for the open frame chassis and VESA mount.



Aluminum bezel is a special design bezel for the open frame chassis.



TrueFlat bezel is a metal bezel with round corners, safety glass and passepartout for the open frame chassis.

Safety glass is an accessory for the open frame chassis. It covers and protects the TFT-panel.



TrueFlat glass is a safety glass with round corners and passepartout for the open frame chassis.


Touches*

| Order number | | DS-91-917 | DS-91-918 |
|---|------------|--|--|
| Name | | TrueFlat bezel PCAP touch | TrueFlat glass PCAP touch |
| Bezel/ Glass | | Sheet steel RAL 9006, safety glass TSG, 4 mm anti-glare, printed black passepartout RAL 9005 | Safety glass TSG, 4 mm anti glare, printed black passepartout (RAL 9005) |
| Touch points | | 10 | |
| Touch technology | | Projected capacitive | |
| Can be combined with | | — | |
| Available for controller | | Video PME, Video PIII, IQ Ontario, IQ Core-i | |
| Weight | [kg/ lb] | 12.0/ 26.45 | 7.5/ 16.53 |
| Dimensions of monitor with option (W x H x D) | [mm/ inch] | 1021 x 614 x 116 40.20 x 24.17 x 4.57 | 1013 x 606 x 115 39.88 x 23.86 x 4.53 |



TrueFlat bezel monitor with PCAP touch sensor

| Order number | | DS-91-503 | DS-91-507 |
|--|------------|--|---|
| Name | | DST touch | IR touch |
| Touch points | | 1 | 6 |
| Touch technology | | Capacitive | Infrared |
| Can be combined with | | Front bezel | |
| Available for controller | | Video PME, Video PIII, IQ Ontario, IQ Core-i | |
| Weight | [kg/ lb] | 3.0/ 6.61 | 5.7/ 12.57 |
| Weight with front bezel | [kg/ lb] | 4.5/ 9.92 | 7.2/ 15.87 |
| Dimensions of monitor with option (W x H x D) | [mm/ inch] | 991 x 583 x 113 39.01 x 22.95 x 4.45 | 991 x 583 x 125 39.01 x 22.95 x 4.92 |
| Dimensions of monitor with option (W x H x D) with front bezel | [mm/ inch] | 994 x 587 x 116 39.13 x 23.11 x 4.57 | 994 x 587 x 126 39.13 x 23.11 x 4.96 |




TrueFlat PCAP touch is a TrueFlat glass with a laminated PCAP touch at the backside.

*Cover glass and touches will reduce monitor brightness.

External PC

| | | |
|--------------------------|--|--|
| Order number | DS-91-426 | DS-427 |
| Name | PC-Box i3 | PC-Box i5 |
| Description | PC Module for external mounting | |
| Interfaces | VGA, DVI, 2x RS232, 2x Ethernet RJ45, 4x USB 2.0, 4x USB 3.0, 3x Audio Jack 3,5mm, 2x PS2 for Mouse and Keyboard | |
| PC | CPU: Intel® Core-i3-(4 x 2.4 GHz), Grafik Intel HD 3000, RAM: 4GB DDR 3, Storage: 120 GB SSD | CPU: Intel® Core-i5 (4 x 3.2 GHz), Grafik Intel HD 3000, RAM: 4GB DDR 3, Storage: 120 GB SSD |
| Available for controller | Video PME, Video PIII | |
| Fan | Fanless operation | |
| Weight [kg/ lb] | 4.8/ 10.58 | |
| Dimensions [mm/ inch] | 344 x 260 x 72/ 13.54 x 10.24 x 2.83 | |

Accessories



Optional removable PC box with Intel Core-i3/5 CPU. The PC box can be removed without taking the display down from the wall.

Electronic

| | | |
|--------------------------|---|---|
| Order number | DS-91-622 | DS-91-905 |
| Name | Soundbar external | WLAN |
| Description | Active speaker kit on the bottom | WLAN modul with antenna |
| Details | 2 x 1.25 Watt, 5V, USB digital audio input, power via USB | Intel Centrino Wireless N2230 IEEE WLAN Standard: 802.11b/g/n up to 300 Mbps/ 2.4 GHz; Safety: WPA (TKIP)/ WPA2 (AES-CCMP) |
| Can be combined with | with all front options except TrueFlat bezel | with all front options |
| Available for controller | IQ Ontario, IQ Core-i, Video-Poster | IQ Core-i |

| Product | Order no. | Product description |
|----------------|-----------|---|
| Power supply | DS-30-690 | Desktop power supply. Necessary to operate a PC box from 31.5" without monitor, 24V/ 120 W |
| Remote control | DS-91-621 | OSD remote controll for all displays of the Video PME and Video PIII Series from 31.5" to 54.6" |



Mounts and Covers

Accessories

| Product | Order no. | Product description |
|----------------------------|-----------|---|
| Wall mount | DS-91-540 | Inclinable wall mount for all displays from 31.5" up to 54.6" |
| Wall mount | DS-91-101 | Titling wall mount for all displays from 46" up to 54.6" |
| Protective cover | DS-91-604 | Installed on top of the display, dust shield prevents liquid or falling dust from penetrating the electronic part of the monitor via the upper air vents |
| Cable cover for connectors | DS-91-723 | Cover for the cable connectors to prevent unauthorized persons from removing or plugging cables. For all POS-Line displays of the PME and PIII Series from 31.5" up to 54.6" |
| Cable cover for connectors | DS-91-578 | Cover for the cable connectors to prevent unauthorized persons from removing or plugging cables. For all POS-Line displays of the IQ Core-i Series from 31.5" up to 54.6". Also suited for optional PC boxes DS-91-426 and DS-91-427. |
| Cable cover for connectors | DS-91-922 | Cable cover. Only available in combination with covers DS-91-723 and DS-91-578. |

Operating systems, Software

| Product | Order no. | Product description |
|--------------------------------|-----------|--------------------------|
| Windows 7 embedded 32 bit DE | DS-60-645 | Operation system |
| Windows 7 embedded 32 bit EN | DS-60-650 | Operation system |
| Windows 7 FES 64 bit DE | DS-60-725 | Operation system |
| Windows 7 FES 64 bit EN | DS-60-781 | Operation system |
| Windows 8.1 embedded 64 bit DE | DS-60-764 | Operation system |
| Windows 10 Pro. 64 bit DE | DS-60-811 | Operation system |
| Windows 10 Pro. 64 bit EN | DS-60-810 | Operation system |
| WEBPOSTER | DS-60-787 | WEBPOSTER embedded Linux |

Various accessories are available for POS-Line monitors.


All monitors can be customized according to your specific requirements.

Please contact our sales team if you are interested in product modifications or custom designs.

POS-Line TrueFlat design with glass or touch



POS-Line open frame



POS-Line with PC box



Data Display Group



DATA Display Group is represented through its own subsidiaries in Germany, the USA and England. Please address all enquiries to the office nearest to you. For sales or service matters we will either handle your enquiry directly, or invite you to contact one of our business partners in your area for assistance.

Distec GmbH
Augsburger Str. 2b
82110 Germering

Distec GmbH
Lauchergasse 6-12
99817 Eisenach

+49 89 894363-0 +49 3691 889398-0
info@datadisplay-group.de
www.datadisplay-group.de

Display Technology Ltd.
5 The Oaks Business Village
Revenge Road, Lordswood
Chatham, Kent, ME5 8LF

+44 1634 672755
info@displaytechnology.co.uk
www.datadisplay-group.co.uk

Apollo Display Technologies, Corp.
87 Raynor Avenue, Unit 1
Ronkonkoma, NY 11779

+1 631 5804360
info@apollodisplays.com
www.apollodisplays.com

Contact



All figures are typical values. The real values of the panel may vary. The optical characteristics are determined after the panel has been „ON“ for approximately 30 minutes at an ambient temperature of 25° C (77° F).

Life time of the backlight is defined as the time to take until the brightness reduces to 50% of its original value.

Copyright 2016 Data Display Group. Information in the document is subject to change without prior notice.