

NL8048BC24-12D

9.0" WVGA
Industrial use
[Features]

- High contrast(900:1)
- 16.77M/262K colors (LVDS RGB 8-bit/6-bit)
- Reversible-scan direction
- Long-life LED backlight^{※1}



Pixel	800(H) x 480(V)
Display area	196.8(H) x 118.08(V) mm 9.0 inches (23cm)
Display color	16,777,216 colors/262,144 colors
Pixel pitch	0.246(H) × 0.246(V) mm
Luminance	450cd/m ² (typ.)
Contrast ratio	900:1 (typ.)
Viewing angle ^{※2}	Up: 80°, Down: 80°, Left: 80°, Right: 80°
Response time ^{※3}	18ms (typ.)
Signal system	LVDS 1-port RGB 8-bit/6-bit
Power supply voltage	3.3V
Power consumption	4.1W (typ.)
Operating temperature	-20°C to +70°C
Storage temperature	-30°C to +80°C
Polarizer surface	Antiglare
Module size	W 220.5 (typ.) x H 136.5 (typ.) x D 8.7 (max.) mm
Weight	275g (typ.)
Backlight	LED backlight (Replaceable)
LED driver	(104PW03F)

※1 70k hours long life LED

※2: Contrast ratio ≥ 10:1

※3: Ton+Toff (10%←→90%)

※All information is subject to change without notice.

※Screen images are simulated.

<NLT Technologies web site>

Japanese <http://www.nlt-technologies.co.jp/jp>

English <http://www.nlt-technologies.co.jp/en>

Last update:11/2015

©NLT Technologies,Ltd. 2011-2015