

[Features]

- High luminance (800cd/m²)
- High contrast (900 : 1)
- 16.77M/262K colors (LVDS RGB 8-bit/6-bit)
- Reversible-scan direction
- Wide temperature (-30°C to +80°C)
- Long-life LED backlight*¹



Pixel	1,024 (H) x 768 (V)
Display area	245.76 (H) x 184.32 (V) mm 12.1 inches (31cm)
Display color	16,777,216 colors/ 262,144 colors
Pixel pitch	0.24(H) x 0.24(V) mm
Luminance	800cd/m ² (typ.)
Contrast ratio	900:1 (typ.)
Viewing angle* ²	Up: 80°, Down: 80°, Left: 80°, Right: 80°
Response time* ³	18ms (typ.)
Signal system	LVDS 1-port RGB 8-bit/6-bit
Power supply voltage	3.3V
Power consumption	7.5W (typ.)
Operating temperature	-30°C to +80°C
Storage temperature	-30°C to +80°C
Polarizer surface	Clear
Module size	W 260.5 (typ.) x H 203.0 (typ.) x D 9.2 (max.) mm
Weight	490g (typ.)
Backlight	LED backlight(Replaceable)
LED driver	104PW03F

*¹ 70k hours long life LED

*² Contrast ratio ≥ 10:1

*³ Ton+Toff (10%←→90%)

*All information is subject to change without notice.

*Screen images are simulated.

<NLT Technologies web site>

Japanese <http://www.nlt-technologies.co.jp/jp>

English <http://www.nlt-technologies.co.jp/en>

Last update:11/2015

©NLT Technologies,Ltd. 2011-2015